AXIAL FAN

CERTIFIED PREMIUM INDUSTRIAL TOOLS

ATEX (Explosive - Atmosphere)

EGA Master offers a wide range of intrinsically safe tools for use in hazardous areas. Among them are axial fans, ideal for ventilation and evacuation in potentially explosive gaseous atmospheres.

Pneumatic



Zones
1, 2 GAS

Ground connection 76073 is mandatory for the safe use of ATEX axial and Venturi fans.


1. Ideal **for ventilation, ships' waste tanks, oily deposits, as well as indoors or underground works**... etc.



2. **Aluminum protection.**

3. Suitable for use in ATEX Areas **II 2G Ex h IIB T6 Gb.**

4. **Ergonomic handle** for an easy transport.



*** 12M** CE



COD.
79620

TECHNICAL SPECIFICATIONS	
Type	Pneumatic
Maximum operating pressure	5 bar
Nominal Ø	300
RPM	2500
Air consumption	0,45 m^3/ min
Sound level	85,7 db(A)
Output air flow	0,57 m^3/s
Length	350
ATEX marking	II 2G Ex h IIB T6 Gb
Weight	13 kg

Accessories not included / For more technical information or accessories check www.egamaster.com

12M 12 MONTHS OF WARRANTY

ACCESSORIES

COD.	Description	Valid for	I.D. mm
79710	Antistatic connecting piece	79620	300



COD.	Description	Valid for	I.D. mm
79711	Antistatic quick-seal coupling	79620	300



COD.	Description	Valid for	I.D. mm
79712	Plastic ducting 5M long, antistatic	79620	300



COD.	Description	Valid for	
76073	Grounding for ATEX fans	79620	1,5

Ground connection 76073 is mandatory for the safe use of ATEX axial and Venturi fans.



This document has been created by and is the property of EGA Master S.L. Thus, all intellectual rights belong to EGA Master. Any total or partial copy of this document in any physical, electronic or any other form is strictly forbidden. EGA Master will legally proceed against any infringement of these rights.