

MASTERVISION ● REC Y ECO



The best ally of electric, plumbing, air-conditioning, automobile, aviation, mechanic repair sectors.



1. Monitor TFT 7" color 320x960 pixel. Sistema antideslumbramiento.



2. Mastervisión REC includes USB recording system.

USB



3. 60060 20m cable. 60061 30m cable.

Marked each meter to know the exact position of the obstruction.




4. Remote control




5. INOX camera Ø26mm with 8 LEDs with adjustable lighting.



Anti-impact case and watertight (IPX8)!



6. Two use possibilities:
- Connected to power supply.
- With battery.



MASTERVISION REC



COD.	V	CAP. (mm)		
60060	110 V- 240 V (50-60 Hz)	Ø 40-Ø 200	20	12
60061			30	

CE I G12

TECHNICAL SPECIFICATIONS

Monitor	320 x 960 Pixel 7" TFT color
Working temperature	-28 °C-50 °C / -18° F -122° F
Case	53,5x22x47,5cm
INOX camera	Ø 26 mm (1")
Cable total length	
	60060 20 m (66')
	60061 30 m (100')
Flexible push rod	
	60060 20 m (66')
	60061 30 m (100')
Pipe inspection	Ø 40-Ø 200 mm
Batteries	12V DC 1800 mA
Waterproof camera	IP X8
Video output	●
USB recording system	●
Card reader	USB
Input voltage	100-240 V
Illumination sensor	COLOR CCD
Depth of view	400 mm
Field of view	60°
White light source	8 LED
1 Gb pendrive with laser pointer	●



MASTERVISION ECO



COD.	V	CAP. (mm)		
60062	110 V- 240 V (50-60 Hz)	Ø 40-Ø 200	20	12
60063			30	

CE I G12

TECHNICAL SPECIFICATIONS

Monitor	320 x 960 Pixel 7" TFT color
Working temperature	-28 °C-50 °C / -18° F -122° F
Case	53,5x22x47,5cm
INOX camera	Ø 26 mm (1")
Cable total length	
	60062 20 m (66')
	60063 30 m (100')
Flexible push rod	
	60062 20 m (66')
	60063 30 m (100')
Pipe inspection	Ø 40-Ø 200 mm
Batteries	12V DC 1800 mA
Waterproof camera	IP X8
Video output	●
USB recording system	●
Card reader	USB
Input voltage	100-240 V
Illumination sensor	COLOR CCD
Depth of view	400 mm
Field of view	60°
White light source	8 LED

ACCESSORIES



COD.	Description	L (m)
60056	Carrete de cable	20
60057		30