

SLOGGING RING WRENCH



Available in mm
and inch





**From 17mm/1/2"
to 200mm/8"!**

1. To tighten or loosen large nuts and bolts in ship-building and other heavy industries, maintenance of industrial plants.

2. Suitable to be used with hammer or mallet.



SLOGGING RING MM



COD.	AF mm	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68927	17							
68928	19	145	32	12	7			
68929	22	155	38	13	8	0,2		
68930	24	165	42	14	9			
68931	27	175	46		10	0,3		
68932	30		50	16		0,4	5	•
68933	32	185	55		11	0,5		
68934	36	210	60	19		0,6		
68935	41	230	65	20	12	0,7		
68936	46	240	75	22	13	1		
68937	50	250	80	23		1,2		
68938	55		85	24	14	1,4		
68939	60	270	90	26	15	1,6		
68940	65	300	100	30	16	1,9		
68941	70	320	105	32	17	2,3		
68942	75	330	115	33	18	2,9		
68943	80	350	125	34	19	3,6		
68944	85	360	130	36	20	3,9		
68945	90	380	135	39	23	4,8	1	-
68946	100	410	148	43	25	5,8		
68947	110	450	170	45	28	8		
68948	120	480	180	50	30	10		
68949	130	510	200	55	31	12		
68950	140	520	210		32	14		
68951	150	570	220	60		14		
68952	160	590	240		33	16		



SLOGGING RING INCH.




COD.	AF Inch	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68687	5/8	145	32	12	7			
68614	3/4					0,2		
68615	7/8	155	38	13	8			
68616	15/16	165	42	14	9			
68617	1	175	46		10	0,3		
68618	1.1/16							
68619	1.1/8			16		0,4	5	•
68620	1.3/16	185	50					
68621	1.1/4		55		11			
68622	1.5/16			18		0,5		
68623	1.3/8	210		19				
68624	1.7/16		60					
68625	1.1/2	220						
68626	1.9/16			20	12	0,7		
68627	1.5/8	230	65					
68628	1.11/16							
68629	1.3/4							
68630	1.13/16	240	75	22	13			
68631	1.7/8					1		
68632	1.15/16	250	80	23				
68633	2							
68634	2.1/16				14			
68635	2.1/8		85	24		1,4		
68636	2.3/16							
68637	2.1/4	270						
68638	2.5/16		90	26	15	1,6		
68639	2.3/8							
68640	2.7/16							
68641	2.1/2							
68642	2.9/16	300	100	30	16	2,3		
68643	2.5/8							
68644	2.11/16							
68645	2.3/4	320	110	32	17	2,5		
68646	2.13/16							
68647	2.7/8							
68648	2.15/16	330	115	33	18	3,2		
68649	3						1	-
68650	3.1/16	350	125	34	19	3,6		
68651	3.1/8							
68652	3.1/4							
68653	3.5/16	360	130	36	20	3,9		
68654	3.3/8							
68655	3.1/2	380	135			4,8		
68656	3.9/16							
68657	3.5/8			39	23			
68658	3.11/16	390	140			5,2		
68659	3.3/4							
68660	3.13/16							
68661	3.7/8	410	150			5,8		
68662	3.15/16			43	25			
68663	4							
68664	4.1/16	420	155			6,5		
68665	4.1/8							
68666	4.3/16							
68667	4.1/4		160			8		
68668	4.5/16	450		45	28			
68669	4.3/8							
68670	4.1/2		170			9,6		
68671	4.9/16							

SLOGGING RING INCH.

COD.		L (mm)	A (mm)	B (mm)	C (mm)			
68672	4.5/8	480	180	50	30	11	1	-
68673	4.11/16							
68674	4.3/4							
68675	4.13/16							
68676	4.7/8							
68677	4.15/16							
68678	5	520	200	55	31	12		
68679	5.1/4							
68680	5.5/16							
68681	5.3/8		210	60	32	14		
68682	5.1/2							
68683	5.3/4		570	220			16	
68684	6	590						

DIN 7444

SLOGGING RING MM



COD.		L (mm)	A (mm)	B (mm)	C (mm)			
67310	17	145	32	12	7	0,2	5	●
67311	18							
67312	19							
67313	20	155	38	13	8			
67314	21							
67315	22							
67316	23	165	42	14	8,5			
60881	24							
67317	25							
60904	26	175	46	16	9,5	0,3	5	●
60882	27							
67318	28							
67319	29	185	50	18	11			
60883	30							
67320	31							
60884	32	210	55	19	12	0,4	5	●
67321	33							
67322	34							
67323	35	220	60	20	13	0,5	5	●
60885	36							
67324	37							
67325	38	215	61	22	14	0,6	1	●
67274	39							
60886	41							
60887	42	225	65	23	14	0,7	1	●
67326	45							
60888	46							
67327	47	240	75	24	14	1	1	●
67422	48							
60889	50							
67328	52	250	80	24	14	1,2	1	●
67329	54							
60890	55							
67330	56	270	85	24	14	1,4	1	●




SLOGGING RING MM

COD.		L (mm)	A (mm)	B (mm)	C (mm)			
67331	58	270	90	24	15	1,4		
67332	59							
60891	60							
67333	61			26		1,6		
67334	62	300	100		16			
67335	63							
67336	64							
60939	65			30		1,9		
67337	66	320	110		17			
67338	67							
67339	68							
67340	69			32		2,3		
60940	70	330	115		18			
67341	71							
67342	72							
67343	73							
67499	74	350	125		19			
60941	75			33		2,9		
67344	76							
67345	77							
67346	78	360	130		20			
67347	79			34		3,6		
60942	80							
67348	82							
67492	84	380	135		23			
60943	85			36		3,9		
67349	88							
60944	90			39		5		
67350	94	390	145		25		1	
60945	95							
67351	98							
60946	100					6		
67308	102	420	155	43	28			
60947	105					6,5		
67309	107					7,0		
67368	108							
60948	110	450	170	45	32	8,0		
60949	115					9,5		
57128	118							
60950	120			50		10		
67352	125	510	195		33			
67353	130							
67354	135			55		12		
67355	140							
67356	145	570	220		34			
67357	150			60		14		
67358	155							
67359	160							
67360	165	590	240		35	16		
67361	170							
67362	175			65		25		
67363	180							
67364	185	690	280	70	36	33		
67365	190							
67366	195							
67367	200			75				

DIN 7444

SLOGGING RING INCH.



COD.	AF Inch	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
67369	1/2	100	24	9	5	0,1		
67370	3/4	145	32	12	7			
69003	13/16	155	38	13	8	0,2		
67371	7/8							
67372	15/16	165	42	14	9			
60983	1							
60984	1.1/16	175	46		10	0,3		
67373	1.1/8			16		0,4		
60985	1.3/16	185	50					
60986	1.1/4				11		5	•
67374	1.5/16		55	18		0,5		
61294	1.3/8	210		19				
67375	1.7/16		60					
61295	1.1/2	220						
61296	1.9/16							
60987	1.5/8	230	65	20	12	0,7		
67376	1.11/16							
67377	1.3/4							
60988	1.13/16	240	75	22	13			
67378	1.7/8					1		
67379	1.15/16	250	80	23				
60989	2				14			
67380	2.1/16					1,4		
67381	2.1/8		85	24				
67382	2.3/16							
67383	2.1/4	270						
67384	2.5/16							
60990	2.3/8		90	26	15	1,6		
67385	2.7/16							
67386	2.1/2							
60991	2.9/16	300	100	28	16	2,3		
67387	2.5/8							
67388	2.11/16							
60992	2.3/4	320	110	32	17	2,5		
67389	2.13/16							
67390	2.7/8							
60993	2.15/16	330	115	33	18	3,2		
60994	3							
67391	3.1/16	350	125	34	19	3,6		
60995	3.1/8						1	-
58071	3.3/16	355	124			3,6		
67392	3.1/4							
67393	3.5/16	360	130	36	20	3,9		
67394	3.3/8							
68570	3.7/16							
67395	3.1/2	380	135			4,8		
67396	3.9/16							
67397	3.5/8			39	23			
67398	3.11/16	390	140			5,2		
60996	3.3/4							
67399	3.13/16							
67400	3.7/8	410	150			5,8		
67401	3.15/16							
60997	4			43	25			
67402	4.1/16	420	155			6,5		
60998	4.1/8							
67403	4.3/16							
67404	4.1/4	450	160	45	28	8		
67405	4.5/16							
67406	4.3/8							



SLOGGING RING INCH.

COD.		L (mm)	A (mm)	B (mm)	C (mm)			
60999	4.1/2	450	170	45	28	9,6		
67407	4.9/16							
67408	4.5/8							
67409	4.11/16							
67410	4.3/4	480	180	50	30	11		
67411	4.13/16							
67412	4.7/8							
67413	4.15/16							
67414	5	520	200	55	31	12		
67415	5.1/4							
67416	5.5/16							
67417	5.3/8							
67418	5.1/2	570	210	60	32	14		
67537	5.5/8							
67419	5.3/4							
67420	6							
57136	6.1/8	590	220			16	1	-
57139	6.1/4	565				13,7		
58055	6.3/8	585	240	58	33	16		
58056	6.1/2							
58057	6.9/16							
58058	6.5/8							
58059	6.3/4	645	265	64	34	25		
58060	6.7/8							
58061	7							
58062	7.1/8							
58063	7.1/4	685	285	70		33		
58064	7.3/8							
58065	7.1/2							
58066	7.9/16							
58067	7.5/8	710	295	75		36		
58068	7.3/4							
58069	7.7/8							
58070	8							

DIN 7444

TECHNICAL SPECIFICATIONS		
MATERIAL	Special steel	
HARDNESS	From 17mm (1/2") to 46mm (1.15/16")	34-40 HRC
	From 50mm (2") to 200mm (8")	30-36 HRC
FINISHING	Painted in epoxi powder matt black color semi-texturized	