SLOGGING RING WRENCH

CERTIFIED PREMIUM INDUSTRIAL TOOLS

Available in mm and inch




From 17mm/1/2" to 200mm/8"!

1. To tighten or loosen large nuts and bolts in ship-building and other heavy industries, maintenance of industrial plants.

2. Suitable to be used with **hammer or mallet.**

SLOGGING RING MM




COD.	AF mm	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68927	17	145	32	12	7	0,2	5	•
68928	19							
68929	22	155	38	13	8			
68930	24	165	42	14	9			
68931	27	175	46	16	10	0,3		
68932	30	185	50		11	0,4		
68933	32		55			0,5		
68934	36	210	60	19		0,6		
68935	41	230	65	20	12	0,7		
68936	46	240	75	22	13	1		
68937	50	250	80	23	14	1,2	1	-
68938	55	270	85	24		1,4		
68939	60		90	26	15	1,6		
68940	65	300	100	30	16	1,9		
68941	70	320	105	32	17	2,3		
68942	75	330	115	33	18	2,9		
68943	80	350	125	34	19	3,6		
68944	85	360	130	36	20	3,9		
68945	90	380	135	39	23	4,8		
68946	100	410	148	43	25	5,8		
68947	110	450	170	45	28	8		
68948	120	480	180	50	30	10		
68949	130	510	200	55	31	12		
68950	140	520	210	60	32			
68951	150	570	220			14		
68952	160	590	240		33	16		



DIN 7444

SLOGGING RING INCH.






COD.	AF inch	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68687	5/8	145	32	12	7	0,2		
68614	3/4							
68615	7/8	155	38	13	8			
68616	15/16	165	42	14	9			
68617	1	175	46	16	10	0,3		
68618	1.1/16							
68619	1.1/8	185	50		11	0,4	5	●
68620	1.3/16							
68621	1.1/4		55	18		0,5		
68622	1.5/16	210						
68623	1.3/8		60	19				
68624	1.7/16							
68625	1.1/2	220		20	12	0,7		
68626	1.9/16	230	65					
68627	1.5/8							
68628	1.11/16							
68629	1.3/4	240	75	22	13	1		
68630	1.13/16							
68631	1.7/8							
68632	1.15/16	250	80	23	14			
68633	2							
68634	2.1/16	270	85	24		1,4		
68635	2.1/8							
68636	2.3/16							
68637	2.1/4		90	26	15	1,6		
68638	2.5/16							
68639	2.3/8							
68640	2.7/16							
68641	2.1/2	300	100	30	16	2,3		
68642	2.9/16							
68643	2.5/8							
68644	2.11/16	320	110	32	17	2,5		
68645	2.3/4							
68646	2.13/16							
68647	2.7/8	330	115	33	18	3,2		
68648	2.15/16							
68649	3						1	-
68650	3.1/16	350	125	34	19	3,6		
68651	3.1/8							
68652	3.1/4	360	130	36	20	3,9		
68653	3.5/16							
68654	3.3/8							
68655	3.1/2	380	135	39	23	4,8		
68656	3.9/16							
68657	3.5/8	390	140			5,2		
68658	3.11/16							
68659	3.3/4							
68660	3.13/16	410	150	43	25	5,8		
68661	3.7/8							
68662	3.15/16							
68663	4	420	155			6,5		
68664	4.1/16							
68665	4.1/8							
68666	4.3/16	450	160	45	28	8		
68667	4.1/4							
68668	4.5/16							
68669	4.3/8							
68670	4.1/2		170			9,6		
68671	4.9/16							

SLOGGING RING INCH.

COD.	AF inch	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
68672	4.5/8	480	180	50	30	11	1	-
68673	4.11/16							
68674	4.3/4							
68675	4.13/16							
68676	4.7/8							
68677	4.15/16							
68678	5	520	200	55	31	12		
68679	5.1/4							
68680	5.5/16							
68681	5.3/8		210	60	32			
68682	5.1/2							
68683	5.3/4	570	220			14		
68684	6	590				16		

DIN 7444

SLOGGING RING MM






COD.	AF mm	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
67310	17	145	32	12	7	0,2	5	●
67311	18							
67312	19							
67313	20	155	38	13	8			
67314	21							
67315	22							
67316	23	165	42	14	8,5			
60881	24							
67317	25							
60904	26	175	46	16	9,5	0,3		
60882	27							
67318	28							
67319	29	185	50			0,4		
60883	30							
67320	31							
60884	32	210	55	18	11	0,5		
67321	33							
67322	34							
67323	35		60	19		0,6		
60885	36							
67324	37	220	60	20	12	0,6	5	
67325	38					0,7		
67274	39	215	61			0.6		
60886	41	225	65			0,7		
60887	42							
67326	45	240	75	22	13	1		●
60888	46							
67327	47							
67422	48	250	80	23	14	1,2	1	
60889	50							
67328	52							
67329	54	270	85	24		1,4		
60890	55							
67330	56							

SLOGGING RING MM

COD.	AF mm	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
67331	58	270	90	24	15	1,4		
67332	59							
60891	60			26		1,6		
67333	61							
67334	62							
67335	63	300	100	30	16	1,9		●
67336	64							
60939	65							
67337	66							
67338	67	320	110	32	17	2,3		
67339	68							
67340	69							
60940	70							
67341	71							
67342	72							
67343	73	330	115	33	18	2,9		
67499	74							
60941	75							
67344	76							
67345	77							
67346	78	350	125	34	19	3,6		
67347	79							
60942	80							
67348	82							
67492	84	360	130	36	20	3,9		
60943	85							
67349	88	380	135	39	23	5	1	
60944	90							
67350	94	390	145					
60945	95							
67351	98	410	150	43	25	6		
60946	100							
67308	102							
60947	105	420	155			6,5		-
67309	107					7,0		
67368	108	450	170	45	28	8,0		
60948	110							
60949	115					9,5		
57128	118	480	180	50	30	10		
60950	120							
67352	125							
67353	130	510	195	55	31	12		
67354	135							
67355	140	520	210	60	32	14		
67356	145	570	220					
67357	150							
67358	155							
67359	160	590	240		33	16		
67360	165							
67361	170	650	270	65	34	25		
67362	175							
67363	180	690	280	70	35	33		
67364	185							
67365	190							
67366	195	710	300	75		36		
67367	200							

DIN 7444

SLOGGING RING INCH.





COD.	AF inch	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
67369	1/2	100	24	9	5	0,1		
67370	3/4	145	32	12	7	0,2		
69003	13/16	155	38	13	8			
67371	7/8							
67372	15/16	165	42	14	9			
60983	1	175	46	16	10	0,3		
60984	1.1/16							
67373	1.1/8	185	50		11	0,4	5	●
60985	1.3/16							
60986	1.1/4		55			0,5		
67374	1.5/16			18				
61294	1.3/8	210	60	19				
67375	1.7/16							
61295	1.1/2	220						
61296	1.9/16	230	65	20	12	0,7		
60987	1.5/8							
67376	1.11/16							
67377	1.3/4	240	75	22	13	1		
60988	1.13/16							
67378	1.7/8							
67379	1.15/16	250	80	23	14			
60989	2							
67380	2.1/16	270	85	24		1,4		
67381	2.1/8							
67382	2.3/16							
67383	2.1/4		90	26	15	1,6		
67384	2.5/16							
60990	2.3/8							
67385	2.7/16							
67386	2.1/2	300	100	28	16	2,3		
60991	2.9/16							
67387	2.5/8							
67388	2.11/16	320	110	32	17	2,5		
60992	2.3/4							
67389	2.13/16							
67390	2.7/8	330	115	33	18	3,2		
60993	2.15/16							
60994	3							
67391	3.1/16	350	125	34	19	3,6	1	-
60995	3.1/8							
58071	3.3/16	355	124	36	20	3.6		
67392	3.1/4	360	130			3,9		
67393	3.5/16							
67394	3.3/8							
68570	3.7/16	380	135	39	23	4,8		
67395	3.1/2							
67396	3.9/16							
67397	3.5/8	390	140			5,2		
67398	3.11/16							
60996	3.3/4							
67399	3.13/16	410	150	43	25	5,8		
67400	3.7/8							
67401	3.15/16							
60997	4	420	155			6,5		
67402	4.1/16							
60998	4.1/8							
67403	4.3/16	450	160	45	28	8		
67404	4.1/4							
67405	4.5/16							
67406	4.3/8							

DIN 7444

SLOGGING RING INCH.

COD.	AF inch	L (mm)	A (mm)	B (mm)	C (mm)	Kg		
60999	4.1/2	450	170	45	28	9,6		
67407	4.9/16							
67408	4.5/8	480	180	50	30	11		
67409	4.11/16							
67410	4.3/4							
67411	4.13/16							
67412	4.7/8							
67413	4.15/16							
67414	5	520	200	55	31	12		
67415	5.1/4							
67416	5.5/16							
67417	5.3/8		210					
67418	5.1/2							
67537	5.5/8	570	220	60	32	14		
67419	5.3/4							
67420	6	590				16		
57136	6.1/8	565				13,7	1	-
57139	6.1/4	585	240	58	33	16		
58055	6.3/8							
58056	6.1/2							
58057	6.9/16							
58058	6.5/8	645	265	64	34	25		
58059	6.3/4							
58060	6.7/8							
58061	7	685	285	70	35	33		
58062	7.1/8							
58063	7.1/4							
58064	7.3/8							
58065	7.1/2							
58066	7.9/16	710	295	75		36		
58067	7.5/8							
58068	7.3/4							
58069	7.7/8							
58070	8							

DIN 7444

TECHNICAL SPECIFICATIONS		
MATERIAL	Special steel	
HARDNESS	From 17mm (1/2") to 46mm (1.15/16")	34-40 HRC
	From 50mm (2") to 200mm (8")	30-36 HRC
FINISHING	Painted in epoxi powder matt black color semi-texturized	

This document has been created by and is the property of EGA Master S.L. Thus, all intellectual rights belong to EGA Master. Any total or partial copy of this document in any physical, electronic or any other form is strictly forbidden. EGA Master will legally proceed against any infringement of these rights.